

SOL-GEL PROCESS UTILIZING REDUCED MIXING TEMPERATURESBackground of the Invention5 Field of the Invention

This invention relates to a sol-gel process for fabricating glass and ceramic monoliths with selected properties (*e.g.*, chemical purity, homogeneity) compatible with a variety of applications, including high-performance optics.

10 Description of the Related Art

High-performance oxide-based materials are increasingly in demand for use in a variety of applications. For example, silica glass has the optical transmittance, mechanical hardness, chemical durability, thermal stability, low thermal expansion, and high laser damage threshold which make it an optimal material for applications such as optoelectronic laser diodes, fiber optic telecommunications, medical laser delivery systems, and military optical sensors. There is significant pressure on material manufacturers to find fabrication techniques which can satisfy the increasingly stringent performance requirements for silica glass and other oxide-based materials.

Numerous techniques are currently in use for the fabrication of glasses or ceramics. For example, silica glasses have traditionally been manufactured by melting natural quartz or synthetic silica in crucibles at high temperatures (typically about 1700° C - 2000° C). However, the resultant materials have limited utility for various optical applications, primarily due to structural inhomogeneities as well as impurity concentrations (*e.g.*, from intrinsic impurities in the raw materials, incomplete chemical reactions of components, and contamination by the crucible). Such high-temperature processes are also unsuitable for manufacturing products with certain compositions, tailored dopant or additive gradients, organic or high vapor pressure additives, or additives in their metallic or partially reduced states.

Another more recent technique for manufacturing silica glasses has been chemical vapor deposition (CVD), in which silicon-containing chemical vapors are combined with oxygen under high temperature conditions to deposit silica onto a

substrate. However, the resultant materials are relatively expensive due to low material collection efficiencies, slow processing rates, and complex processing and pollution control equipment. Furthermore, CVD processes lack the versatility for fabricating more compositionally complex glasses.

5 Sol-gel technology has been used to fabricate products which satisfy some or all of the desired performance requirements without the difficulties or limitations found in more conventional fabrication techniques. A typical sol-gel silica process involves the transition of a liquid colloidal solution "sol" phase into a solid porous "gel" phase, followed by drying and sintering the resulting gel monolith at elevated temperatures to
10 form silica glass. One method of preparing a silica porous gel monolith is to pour into a mold a solution of silica-forming compounds (*e.g.*, silicon alkoxides), solvents, and catalysts, which then undergoes hydrolysis and polymerization, resulting in a wet porous gel monolith or matrix. After drying the wet gel monolith in a controlled environment to remove the fluid from the pores, the dry gel monolith is densified into a
15 solid glass-phase monolith.

Sol-gel technology can yield products with the desired chemical purity, homogeneity, and flexibility in compositions, dopants, and dopant profiles. However, the potential for sol-gel processes for fabricating large monoliths has been limited by various problems. Large gel monoliths can take a long time to dry, thereby limiting the
20 product throughput. But even more importantly, shrinkage of the gel monolith during the drying process often results in cracking, especially in larger gel monoliths.

As outlined by Pope, et al. in U.S. Patent No. 5,023,208 and Wang, et al. in U.S. Patent No. 5,264,197, both of which are incorporated by reference herein, this resultant cracking of gel monoliths during the drying step of the fabrication process is believed to
25 result from stresses due to capillary forces in the gel pores. Numerous techniques for reducing this cracking have been proposed, and many of these efforts have focused on increasing the pore sizes of the gel monolith to reduce the capillary stresses generated during drying. Pope, et al. discloses subjecting the gel to a hydrothermal aging treatment which causes silica particles to migrate and fill small pores in the porous gel
30 matrix, thereby increasing the average pore size. Wang, et al. discloses adjusting the relative concentrations of an alcohol diluent and/or one or more catalysts such as HCl or

HF, which has the effect of increasing the average pore radius of the resulting dry gel. HF catalyzed gels generally have larger pore sizes than gels catalyzed by other catalysts such as HCl, HNO₃, H₂SO₄, or oxalic acid.

5

Summary of the Invention

According to one aspect of the present invention, a method of forming a gel monolith comprises preparing a first solution comprising metal alkoxide and preparing a second solution comprising a catalyst. A third solution is prepared by mixing the first solution and the second solution together. At least one of the first, second, and third solutions is cooled to achieve a mixture temperature for the third solution which is substantially below room temperature, wherein the third solution has a significantly longer gelation time at the mixture temperature as compared to a room temperature gelation time for the third solution. The third solution is allowed to gel, thereby forming the gel monolith.

15 In another aspect of the present invention, a method of processing a solution comprising a catalyst, water, and metal alkoxide comprises extending a gelation time of the solution by keeping the solution at a predetermined temperature substantially below room temperature.

In yet another aspect of the present invention, a solution for a gel monolith comprises a catalyst with a concentration greater than approximately 3 mole % of the solution.

20 In yet another aspect of the present invention, a method of preparing a solution for forming a gel monolith comprises providing a first solution comprising metal alkoxide. The method further comprises providing a second solution comprising a catalyst. The method further comprises mixing the first solution and the second solution together to form a third solution. The method further comprises cooling at least one of the first, second, and third solutions to achieve a mixture temperature for the third solution which is substantially below room temperature. The third solution has a significantly longer gelation time at the mixture temperature as compared to a room temperature gelation time for the third solution.

30

In a further aspect of the present invention, a monolith has a mean pore size of at least 300 Å and a standard deviation from such mean of less than approximately 50 Å.

Brief Description of the Drawings

5 These and other aspects of the present invention will be apparent to the skilled artisan from the following detailed description read in conjunction with the appended drawings, which are meant to illustrate, and not to limit, the invention, and in which:

 Figure 1 is a flow diagram of a method of forming a gel monolith in accordance with an embodiment of the present invention.

10 Figure 2 is a flow diagram corresponding to another embodiment of the present invention in which the first solution is formed by mixing metal alkoxide with a solvent and cooling the first solution.

 Figures 3A-3F schematically illustrate various embodiments of the present invention in which the first solution is mixed and cooled.

15 Figure 4 is a flow diagram corresponding to another embodiment of the present invention in which the second solution is formed by mixing the catalyst with water and cooling the second solution.

 Figure 5 is a flow diagram corresponding to another embodiment of the present invention in which the metal alkoxide is cooled to a first temperature, the second solution is formed by mixing the catalyst, solvent, and water, and cooling the second solution.

 Figure 6 is a flow diagram corresponding to another embodiment of the present invention in which the third solution is formed by mixing the first solution and the second solution, and cooling the third solution.

25 Figure 7 schematically illustrates a mixing station in accordance with embodiments of the present invention.

 Figure 8 schematically illustrates an alternative mixing station in accordance with embodiments of the present invention.

Detailed Description of the Preferred Embodiment

During the drying of a large gel monolith, the gel monolith shrinks in size, and capillary forces in the gel pores arise as the liquid content of the gel monolith is reduced. The tendency of gel monoliths to develop cracks is dependent on these capillary forces. For example, U.S. Patent Application No. 09/615,628 by Wang, et al., entitled "Sol-Gel Process for Production of Oxide-Based Glass and Ceramic Articles," which is incorporated by reference herein, discloses a process that reduces the influence of these forces. The process comprises removing liquid from the pores of the gel monolith such that the outer region of the gel monolith is not dried before the inner region of the gel monolith is dried, thereby avoiding inhomogeneities in the capillary forces which cause stresses and cracking of the gel monolith.

Because the magnitude of the capillary forces is a function of the sizes of the pores in the gel monolith, the tendency for cracking of gel monoliths may be reduced by tailoring the gel microstructure so as to produce gel monoliths with larger pore sizes. The microstructure of a gel monolith is influenced by the rates of hydrolysis and of polymerization which occur simultaneously during the gelation of the wet gel monolith from the sol. For example, in the case of a silica-based sol in which tetraethyl-orthosilicate or TEOS $((C_2H_5O)_4Si)$ is mixed with deionized water, a diluent or solvent such as ethyl alcohol or ethanol (C_2H_5OH) , and a catalyst such as HF or ammonia, hydrolysis occurs with the following reaction: $(C_2H_5O)_4Si + 4H_2O \rightarrow 4C_2H_5OH + Si(OH)_4$. The $Si(OH)_4$ molecules polymerize, resulting in a network of SiO_2 and water. Numerous factors influence the kinetics of hydrolysis and polymerization, including the type and concentration of any catalysts and the temperature. The influence of the catalyst concentration on the pore sizes of the resultant gel monoliths is illustrated by Wang, et al. in U.S. Patent No. 5,264,197. Wang, et al. disclose that increasing the HF catalyst concentration, while maintaining constant concentrations of other constituents of the sol, results in an increase in the average pore radius of the resulting dry gel.

Catalysts such as HF or ammonia increase the rate of hydrolysis and polymerization. If the catalyst concentration is too high, the hydrolysis and polymerization reactions are so fast that the gelation time is extremely short, and in certain circumstances can be nearly instantaneous. Gelation time as used herein is

defined as the time from the moment a sol comprising water and a silicon-containing material such as TEOS is prepared to the moment the sol forms a gel which does not flow. Very short gelation times do not provide sufficient time to allow a prepared sol to be poured into molds for casting, eventual gelation, and further processing. In addition, bubbles which form during the gelation process may not have an opportunity to diffuse out of the gel if the gelation time is short, thereby degrading the quality of the resulting gel. Furthermore, higher temperatures have the effect of shortening the gelation time even further.

Figure 1 is a flow diagram of a method 100 of forming a gel monolith in accordance with an embodiment of the present invention. While the flow diagram of Figure 1 illustrates a particular embodiment with steps in a particular order, other embodiments with different orders of steps are also included in the present invention.

In the embodiment described in Figure 1, in an operational block 110, a first solution 10 is prepared, the first solution 10 comprising metal alkoxide. Examples of metal alkoxides compatible with embodiments of the present invention include, but are not limited to, silicon alkoxides (such as tetramethylorthosilicate (TMOS) or tetraethylorthosilicate (TEOS)), germanium alkoxides (such as tetraethylorthogermanium (TEOG)), aluminum alkoxides, zirconium alkoxides, and titanium alkoxides. In certain embodiments, the first solution 10 comprises more than one metal alkoxide (e.g., both TEOS and TEOG). In certain embodiments, the first solution 10 further comprises a solvent. Examples of solvents include, but are not limited to, ethyl alcohol, methyl alcohol, or other alcohols.

In an operational block 120, a second solution 20 is prepared, the second solution 20 comprising a catalyst. Examples of catalysts include, but are not limited to, hydrofluoric acid (HF) and ammonia (NH₃). In certain embodiments, the second solution 20 further comprises a solvent, examples of which include, but are not limited to ethyl alcohol, methyl alcohol, or other alcohols.

In an operational block 130, a third solution 30 is prepared by mixing the first solution 10 and the second solution 20 together. While in certain embodiments, the second solution 20 further comprises water, in other embodiments, water is added to the third solution 30 such that the third solution 30 thereby comprises water and metal

alkoxide. The third solution 30 can then begin to undergo the hydrolysis and polymerization reactions which form the gel. The presence of the catalyst in the third solution 30 accelerates the formation of the gel (i.e., reduces the gelation time of the third solution 30 as compared to the gelation time without the catalyst) as described above. In an operational block 140, at least one of the first solution 10, second solution 20, and third solution 30 is cooled to achieve a mixture temperature for the third solution which is substantially below room temperature. In certain embodiments, only the third solution 30 is cooled to achieve a mixture temperature which is substantially below room temperature. Such a mixture temperature serves to decelerate the formation of the gel, such that the third solution 30 has a significantly longer gelation time at the mixture temperature as compared to a room temperature gelation time for the third solution 30. In this way, cooling the third solution 30 to the mixture temperature makes it possible to increase the catalyst concentration in the third solution 30 while reducing the problematic effects associated with higher catalyst concentrations. In an operational block 150, the third solution 30 is allowed to gel, thereby forming the gel monolith.

In certain embodiments, as illustrated in the flow diagram of Figure 2, preparing 110 the first solution 10 comprises an operational block 112 in which metal alkoxide is mixed with a solvent to form the first solution 10 and an operational block 114 in which the first solution 10 is cooled to a first temperature substantially below room temperature. While Figure 2 illustrates a particular embodiment in which mixing 112 occurs before cooling 114, in other embodiments one or both of the mixed constituents of the first solution 10 (i.e., the metal alkoxide and the solvent) can be cooled before or while being mixed together to form the first solution 10.

In certain embodiments, mixing 112 the metal alkoxide with the solvent is achieved by pouring both constituents of the first solution 10 into a first vessel 11. In other embodiments, a mixing system 12 is used to agitate the first solution 10 to ensure sufficiently homogeneous mixing of the metal alkoxide and the solvent. Examples of mixing systems 12 in accordance with embodiments of the present invention include, but are not limited to, magnetic stirrers, mechanical stirrers, static mixers, or other mechanisms to agitate the first solution 10. In the embodiment schematically illustrated in Figure 3A, the mixing system 12 comprises a magnetic stirrer which includes a stir

bar 13 comprising a ferromagnetic material and a magnetic driver 14 coupled to the stir bar 13. Upon activation, the magnetic driver 14 generates magnetic forces to spin the stir bar 13 within the first solution 10 for a predetermined period of time. In other embodiments, as schematically illustrated in Figure 3C (discussed more fully below), the mixing system 12 comprises a mechanical stirrer 15 which is inserted into the first solution 10, activated to agitate the first solution 10 for a predetermined period of time, then removed from the first solution 10.

In certain embodiments, the first temperature is preferably approximately equal to or less than 0° C, more preferably approximately equal to or less than -10° C, still more preferably approximately equal to or less than -25° C, and most preferably approximately equal to or less than -40° C. In certain embodiments in which the first temperature is approximately equal to or less than 0° C, the first solution 10 can be cooled in a first vessel 11 placed in an ice bath 16 comprising a mixture of water and ice, as schematically illustrated in Figure 3A. In still other embodiments, the first solution 10 can be cooled in a first vessel 11 contained within a refrigerator 17, as schematically illustrated in Figure 3B. One example of a refrigerator 17 compatible with embodiments of the present invention is an Isotemp General Purpose Lab Refrigerator available from Fisher Scientific International of Hampton, New Hampshire.

In certain embodiments in which the first temperature is approximately equal to or less than -10° C, the first solution 10 can be cooled in a first vessel 11 placed in a glycol bath 18 comprising a mixture of propylene glycol or ethylene glycol and water, typically in approximately equal proportions. In certain embodiments, as schematically illustrated in Figure 3C, the glycol bath 18 is coupled to a chiller 19 which removes heat from the glycol bath 18 to maintain the desired first temperature. One example of a chiller 19 compatible with embodiments of the present invention is an RTE-140 Low Temperature Bath Circulator from Thermo Neslab of Portsmouth, New Hampshire. In other embodiments in which the first temperature is approximately equal to or less than -25° C, the first solution 10 can be cooled in a first vessel 11 contained within a freezer 22, as schematically illustrated in Figure 3D. One example of a freezer 22 compatible with embodiments of the present invention is an Isotemp General Purpose Lab Freezer available from Fisher Scientific International of Hampton, New Hampshire.

In certain embodiments in which the first temperature is approximately equal to or less than -40°C , the first solution 10 can be cooled in a first vessel 11 placed in a dry ice bath 23 comprising a mixture of dry ice (CO_2), propylene glycol or ethylene glycol, and water, as schematically illustrated in Figure 3E. Typically, the dry ice bath 23 comprises equal amounts of propylene glycol or ethylene glycol, and water, and a sufficient amount of dry ice to reduce the temperature of the dry ice bath 23 to the desired level. In other embodiments, the first solution 10 can be cooled by bubbling nitrogen vapor 24 from a liquid nitrogen reservoir 25 through the first solution 10, as schematically illustrated in Figure 3F.

As illustrated in the flow diagram of Figure 4, in certain embodiments, preparing 120 the second solution 20 comprises an operational block 122 in which the catalyst is mixed with water to form the second solution 20 and an operational block 124 in which the second solution 20 is cooled to a second temperature substantially below room temperature. While Figure 4 illustrates a particular embodiment in which mixing 122 occurs before cooling 124, in other embodiments one or both of the mixed constituents of the second solution 20 (i.e., the catalyst and the water) are cooled before or while being mixed together.

In certain embodiments, mixing 122 the catalyst with water is achieved by pouring both constituents of the second solution 20 into a second vessel. Similarly to the mixing 112 of the metal alkoxide with the solvent to form the first solution 10, in other embodiments, a stirring system can be used to agitate the second solution 20 to ensure sufficiently homogeneous mixing of the catalyst and water. Examples of stirring systems in accordance with embodiments of the present invention include, but are not limited to, magnetic stirrers, mechanical stirrers, static mixers, or other mechanisms to agitate the second solution 20.

In certain embodiments, the second temperature is preferably approximately equal to or less than 0°C , more preferably approximately equal to or less than -10°C , still more preferably approximately equal to or less than -25°C , and most preferably approximately equal to or less than -40°C . In certain embodiments in which the second temperature is approximately equal to or less than 0°C , the second solution 20 can be cooled in the second vessel placed in an ice bath 16 or contained in a refrigerator 17, as

described above in relation to the cooling of the first solution 10. Similarly, in
embodiments in which the second temperature is approximately equal to or less than
-10° C, a glycol bath 18 and chiller 19 can be used, in embodiments in which the second
temperature is approximately equal to or less than -25° C, a freezer 22 can be used, and
in embodiments in which the second temperature is approximately equal to or less than
-40° C, a dry ice bath 23 can be used. In addition, in other embodiments, the second
solution 20 can be cooled by bubbling nitrogen vapor 24 from a liquid nitrogen
reservoir 25 through the second solution 20.

In certain embodiments, the first solution 10 can comprise metal alkoxide and
the second solution 20 can comprise the catalyst, solvent, and water. In such an
embodiment, as illustrated in the flow diagram of Figure 5, preparing the first
solution 10 comprises cooling the metal alkoxide to a first temperature substantially
below room temperature in an operational block 116. In such an embodiment,
preparing the second solution 20 comprises mixing the catalyst, solvent, and water
to form the second solution 20 in an operational block 126, and cooling the second
solution 20 to a second temperature substantially below room temperature in an
operational block 128. Embodiments such as that illustrated in Figure 5 avoid having
the water freeze which would inhibit sufficient mixing and further processing of the gel
monolith, for example in embodiments in which the second temperature is
approximately equal to or less than -25° C. Other embodiments for preparing the first
solution 10 and second solution 20 include other procedures for cooling the first
solution 10 and second solution 20 without freezing any of the constituents.

As illustrated in the flow diagram of Figure 6, in certain embodiments, preparing
the third solution 30 comprises an operational block 132 in which the first solution
10 is mixed with the second solution 20 to form the third solution 30. In certain
embodiments, mixing the first solution 10 and second solution 20 is achieved by
pouring both solutions 10, 20 into a third vessel 55. Alternatively in other
embodiments, the first solution 10 is maintained at a temperature substantially below
room temperature while being transferred to the third vessel 55 via a material
measurement system 60.

As schematically illustrated in Figure 7, the material measurement system 60 of certain embodiments comprises an input valve 62, a measuring vessel 64, a scale 66, and an output valve 68. In certain embodiments, the input valve 62 is adjustable and coupled to a proportional-integral-differential (PID) controller (not shown) to control the flow of the first solution 10 into the measuring vessel 64. The scale 66 of certain embodiments is a weight scale which provides a measure of the amount of the first solution 10 in the measuring vessel 64. The output valve 68 of certain embodiments is coupled to a solenoid (not shown) which opens and closes the output valve 68 in response to signals. In certain embodiments, the second solution 20 is transferred to the third vessel 55 via a second material measurement system 70. The second material measurement system 70 can be similar to the material measurement system 60 for the first solution 10, i.e., comprising a second input valve 72, a second measuring vessel 74, a second scale 76, and a second output valve 78, as schematically illustrated in Figure 7. Other embodiments of the material measurement system 60 do not comprise a scale 66 or a second scale 76.

Similarly to the mixing 112 of the metal alkoxide with the solvent to form the first solution 10, in other embodiments, a stirring system can be used to agitate the third solution 30 to ensure sufficiently homogeneous mixing of the first solution 10 and second solution 20. Examples of stirring systems in accordance with embodiments of the present invention include, but are not limited to, magnetic stirrers, mechanical stirrers, static mixers, or other mechanisms to agitate the third solution 30.

At least one of the first solution 10, second solution 20, and third solution 30 is cooled 140 to achieve a mixture temperature for the third solution 30 which is substantially below room temperature. As illustrated in an operational block 142 of Figure 6, in certain embodiments, the third solution 30 is cooled 142 to the mixture temperature concurrently with mixing 132 the first solution 10 with the second solution 20. In the embodiment schematically illustrated in Figure 7, the third vessel 55 is in a glycol bath 18 coupled to a chiller 19 to maintain the third solution 30 at a temperature substantially below room temperature during mixing. While Figure 6 illustrates a particular embodiment in which mixing 132 occurs concurrently with cooling 142, in other embodiments cooling 140 the third solution 30 occurs after mixing 132, or one or

both of the mixed constituents of the third solution 30 (i.e., the first solution 10 or the second solution 20) are cooled before being mixed together.

Once the first solution 10 and the second solution 20 are mixed together, the metal alkoxide of the first solution 10 and the water of the second solution 20 begin to
5 undergo exothermic hydrolysis and polymerization reactions which result in the formation of the gel monolith. The presence of a catalyst, such as HF, increases the reaction rates of these hydrolysis and polymerization reactions, thereby reducing the gelation time. With the temperature of the third solution 30 increasing due to the exothermic reactions, the reaction rates of these reactions increase even further, thereby
10 reducing the gelation time even further. As described above, due to the combination of high catalyst concentrations and increased heat from the exothermic reactions, the hydrolysis and polymerization reaction rates can become too fast (i.e., the gelation time is too short) to allow sufficient processing of the gel monolith resulting from the third solution 30. Therefore, in embodiments of the present invention in which the third
15 solution 30 comprises a catalyst, the third solution 30 is cooled 142 to a mixture temperature substantially below room temperature concurrently with the mixing 132 to reduce the heat available to the hydrolysis and polymerization reactions and to slow down the kinetics of these reactions. At the mixture temperature, the third solution 30 has a longer gelation time as compared to its gelation time at room temperature.

20 In certain embodiments, the mixture temperature is preferably approximately equal to or less than 0° C, more preferably approximately equal to or less than -10° C, still more preferably approximately equal to or less than -25° C, and most preferably approximately equal to or less than -40° C. In certain other embodiments, the third solution 30 is cooled to a mixture temperature at which the gelation time of the third
25 solution 30 is increased by at least ten times as compared to the gelation time of the third solution 30 at room temperature. In certain embodiments in which the mixture temperature is approximately equal to or less than 0° C, the third solution 30 can be cooled using an ice bath 16 or a refrigerator 17, as described above in relation to the cooling of the first solution 10. Similarly, in embodiments in which the mixture
30 temperature is approximately equal to or less than -10° C, a glycol bath 18 and chiller 19 can be used, in embodiments in which the mixture temperature is approximately equal

to or less than -25° C, a freezer 22 can be used, and in embodiments in which the mixture temperature is approximately equal to or less than -40° C, a dry ice bath 23 can be used. In addition, in other embodiments, the third solution 30 can be cooled by bubbling nitrogen vapor 24 from a liquid nitrogen reservoir 25 through the third solution 30.

In certain embodiments, the third solution 30 is allowed to gel, thereby forming the gel monolith, as illustrated in the operational block 150 of the flow diagram of Figure 1. The cooled third solution 30 is poured into a mold 75 in certain embodiments, where the hydrolysis and polymerization reactions are allowed to continue so that the third solution 30 gels into the gel monolith. In certain other embodiments, the third solution 30 is prepared by mixing the first solution 10 and second solution 20 in the mold 75, and cooling the third solution 30 in the mold 75 while the third solution 30 continues to gel to form the gel monolith.

In still other embodiments, as schematically illustrated in Figure 7, the third solution 30 is transferred from the third vessel into a series of molds 75 at approximately 20° C via cooled pumps 80 and cooled filters 90. In certain embodiments, the pumps 80 are either cooled or insulated to prevent the temperatures of the third solution 30 from increasing while flowing to the molds 75. One example of a pump 80 compatible with embodiments of the present invention is Type Number UND1.300TT.18, available from KNF Neuberger, Inc. of Trenton, New Jersey.

The filters 90 remove particles from the third solution 30 which would degrade the quality of the resultant gel monolith. These particles can be contaminants or can be due to pre-gelling of small amounts of the third solution 30. In certain embodiments, each filter 90 comprises multiple filters, which can be chosen to remove particles within certain size ranges. For example, a filter 90 can comprise a 0.6 µm filter connected in series with a 0.1 µm filter. In certain embodiments, the filters 90 are cooled or insulated to prevent the temperatures of the third solution 30 from increasing while flowing therethrough. Exemplary filters 90 compatible with embodiments of the present invention are available from Millipore Corporation of Bedford, Massachusetts.

Figure 8 schematically illustrates a mixing station 300 compatible with embodiments of the present invention in which the first solution 10 and second solution

20 are each prepared in a first vessel 310 and second vessel 320, respectively. In the embodiment schematically illustrated in Figure 8, the first vessel 310 is cooled by a first glycol bath 312 which is maintained at a first temperature by a chiller 314. Similarly, the second vessel 320 is cooled by a second glycol bath 322 which is maintained at a second temperature by a chiller 324. In certain other embodiments, the first temperature and second temperature are approximately equal, and the first solution 10 and second solution 20 are cooled to the same temperature by a single bath. In addition, as described above, other types of baths or cooling procedures to reduce the temperatures of the first solution 10 and second solution 20 are in accordance with embodiments of the present invention.

In certain embodiments, the first vessel 310 is coupled to a static mixer 330 via a first fluid conduit 331 comprising a first valve 332 and a first pump 333, and the second vessel 320 is coupled to the static mixer 330 via a second fluid conduit 334 comprising a second valve 335 and a second pump 336. As schematically illustrated in Figure 8, the first solution 10 is pumped through the first fluid conduit 331 from the first vessel 310 by the first pump 333 upon opening the first valve 332. Similarly, the second solution 20 is pumped through the second fluid conduit 334 from the second vessel 320 by the second pump 336 upon opening the second valve 335. In certain embodiments, the first fluid conduit 331 and second fluid conduit 334 are either cooled or insulated to prevent the temperatures of either the first solution 10 or second solution 20 from increasing while flowing to the static mixer 330.

Certain embodiments comprise an in-line static mixer 330, as schematically illustrated in Figure 8, which has various mixing elements to generate vortices as the fluid flows through the static mixer 330, thereby providing an efficient mixing of the fluids flowing therethrough. Exemplary static mixers 330 compatible with embodiments of the present invention are available from Cole-Parmer Instrument Company of Vernon Hills, Illinois. In certain embodiments, the static mixer 330 is either cooled or insulated to prevent the temperature of the third solution 30 from increasing while being mixed in the static mixer 330.

In the embodiment schematically illustrated in Figure 8, the mixing station 300 further comprises a cooling coil 340 coupled to the static mixer 330 via a third pump

342. In certain embodiments, the cooling coil 340 is a thin-walled tube placed in a third glycol bath 344 which is coupled to a third chiller 345. The thin walls of the cooling coil 340 permit heat transfer from the third solution 30 to the third glycol bath 344, thereby achieving a mixture temperature for the third solution 30 substantially below room temperature. In addition, as described above, other types of baths or cooling procedures to reduce the mixture temperature of the third solution 30 are in accordance with embodiments of the present invention.

In the embodiment schematically illustrated in Figure 8, the mixing station 300 comprise a filter 350 coupled to the cooling coil 340. In certain embodiments, the filter 350 comprises multiple filters, which can be chosen to remove particles within certain size ranges. For example, the filter 350 can comprise a 0.6 μ m filter connected in series with a 0.1 μ m filter. In certain embodiments, the filter 350 is cooled or insulated to prevent the temperatures of the third solution 30 from increasing while flowing therethrough. Exemplary filters 350 compatible with embodiments of the present invention are available from Millipore Corporation of Bedford, Massachusetts.

In the embodiment schematically illustrated in Figure 8, the third solution 30 flows through the filter 350 to the mold 360, which is in a fourth glycol bath 362 coupled to a fourth chiller 363. Alternatively in other embodiments, the mold 360 is at approximately room temperature. Once in the mold 360, the third solution 30 is permitted to gel, thereby forming the gel monolith. In addition, as described above, other types of baths or cooling procedures to reduce the temperature of the third solution 30 are in accordance with embodiments of the present invention.

In certain other embodiments, because of the corrosive nature of the constituents of the third solution 30 (e.g., the hydrogen fluoride catalyst), some or all of the components of the mixing station 300 have their internal portions coated with a protective material. Examples of protective materials in accordance with embodiments of the present invention include, but are not limited to, Teflon® available from E.I. DuPont de Nemours & Co. of Wilmington, Delaware or Kynar® available from Elf Atochem North America of Philadelphia, Pennsylvania.

In certain other embodiments, some or all of the valves, pumps, and chillers are controlled by a control system comprising a microprocessor. In response to user input,

the control system can regulate the timing and duration of the flow of the first solution 10, second solution 20, and third solution 30, as well as the temperatures of these solutions.

By preparing the third solution 30 at a mixture temperature substantially below
5 room temperature, embodiments of the present invention allow higher percentages of catalyst in the third solution 30 without having gelation times which inhibit further processing of the gel monolith. For example, the gelation time for a third solution 30 comprising approximately 3.7 mole % of HF at room temperature is on the order of 100 to 200 seconds. Typically, a gelation time greater than approximately 5 minutes is
10 required to pour the third solution 30 into a mold and to permit bubbles to diffuse out of the third solution 30, thereby avoiding difficulties in the processing of the gel monolith. When processing larger quantities of solution (e.g., during production runs), the time required to process the solution can be even longer. However, by preparing the same third solution 30 comprising approximately 3.7 mole % of HF at -14° C, the gelation
15 time is on the order of 10 to 30 minutes. By preparing the third solution 30 at -40° C, the third solution 30 can comprise approximately 10 mole % of HF before the gelation time is shortened to 10 minutes.

As described above, higher percentages of the catalyst result in larger pore sizes in the resultant gel monolith, thereby reducing the capillary stresses generated during
20 drying of the gel monolith. For example, a third solution 30 comprising approximately 3.7 mole % of HF results in a gel monolith with pore sizes of approximately 500 Å, while a third solution 30 comprising approximately 7.4 mole % of HF results in a gel monolith with pore sizes of approximately 1150 Å.

In certain embodiments, the third solution 30 comprises preferably greater than
25 approximately 3 mole % of a catalyst, more preferably greater than 5 mole % of a catalyst, and most preferably greater than 10 mole % of a catalyst. In certain embodiments, the third solution 30 comprising greater than approximately 3 mole % of the catalyst is cooled to have a gelation time greater than approximately five minutes. In certain other embodiments, the third solution 30 comprising greater than
30 approximately 3 mole % of a catalyst is cooled to have a gelation time greater than one hour. In still other embodiments, the third solution 30 comprising greater than

approximately 3 mole % of a catalyst is cooled to have a gelation time greater than two hours.

Monoliths produced using chemical-vapor deposition techniques typically have pore size distributions which range from approximately 1000 Å to 2000 Å (i.e., with standard deviations of approximately 500 Å). In certain embodiments, the third solution 30 can result in gel monoliths with pore size distributions with mean pore sizes of approximately 1000 Å, but with smaller standard deviations than those obtained using chemical-vapor deposition techniques. In certain embodiments, the resultant gel monolith comprises a distribution of pore sizes having a mean pore size of at least 300 Å and a standard deviation of less than approximately 50 Å.

In an exemplary embodiment, a first solution 10 comprising approximately 900 grams of TEOS, approximately 117 grams of TEOG, and approximately 440 grams of ethanol is prepared and stored in a freezer 22 at a temperature of approximately -30° C for approximately 10 hours. A second solution 20 comprising approximately 110 grams of ethanol, approximately 165 grams of water, and approximately 50 grams of HF is also prepared and stored in the freezer 22 at a temperature of approximately -30° C for approximately 10 hours. The first solution 10 and the second solution 20 are then mixed together using a magnetic stirrer in a vessel in a glycol bath 18 coupled to a chiller 19 whereby the temperature of the resultant third solution 30 is maintained between approximately -10° C and -15° C. After mixing for approximately five minutes, the third solution 30 is pumped into a mold 75 through a filter 80 comprising a 0.6 µm filter and a 0.1 µm filter. The mold 75 is then moved to a flat and safe area at approximately room temperature where the third solution 30 sits and forms a gel monolith. After the third solution 30 forms the gel monolith, ethanol is poured onto the gel monolith to prevent cracking due to the reaction heat generated inside the gel monolith body. All the steps of this exemplary embodiment are performed in a class 1000 or better clean room environment in which the temperature is maintained at approximately 68° F and the humidity is between approximately 35% and 55%.

Although described above in connection with particular embodiments of the present invention, it should be understood the descriptions of the embodiments are illustrative of the invention and are not intended to be limiting. Various modifications and

applications may occur to those skilled in the art without departing from the true spirit and scope of the invention as defined in the appended claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240